2-2061348-0 ACTIVE

FullAXS

TE Internal #: 2-2061348-0


Rugged Fiber Cable Assemblies, Fiber Optic Cable (FOCAB), .216 in [5.5 mm] Diameter, 2 Fibers, Blue, Blue, Black Cable, Standard

Boot Type (Left)

View on TE.com >



Fiber Optics > Fiber Optic Cable Assemblies > Rugged Fiber Cable Assemblies



Fiber Optic Cable Type: Fiber Optic Cable (FOCAB)

Cable Assembly Fiber Diameter: 9/125 µm
Outside Cable Diameter: 5.5 mm [.216 in]

Number of Fibers: 2

Connector Color (End A): Blue

Features

Product Type Features

| Protection & Strain Relief Accessory Type | Protective Cap |
|---|-----------------------------------|
| Fiber Optic Cable Type | Fiber Optic Cable (FOCAB) |
| Fiber Optic Mode | Singlemode |
| Cable Assembly Type | LC with ODVA Adapter to LC Duplex |
| Cable Assembly (End A) | LC with ODVA Adapter Plug |
| Cable Assembly (End B) | LC Duplex Plug |
| Fiber Type | SM |

Configuration Features

| Exit Angle to Exit Angle | 180° to 180° |
|--------------------------|--------------|
| Number of Fibers | 2 |
| Cable Buffering | Tight Buffer |

Body Features

| Connector Color (End A) | Blue |
|-------------------------|---------------|
| Connector Color (End B) | Blue |
| Cable Color | Black |
| Boot Type (Left) | Standard |
| Boot Type (Right) | Bend Limiting |
| Boot Color (Left) | Black |
| | |



| Boot Color (Right) | Blue |
|-------------------------------|-----------------|
| Dimensions | |
| Cable Assembly Fiber Diameter | 9/125 μm |
| Outside Cable Diameter | 5.5 mm[.216 in] |
| Other | |
| Cable Assembly Length | 19.8 – 20.2 m |

Product Compliance

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU | Compliant with Exemptions |
|---|--|
| EU ELV Directive 2000/53/EC | Compliant with Exemptions |
| China RoHS 2 Directive MIIT Order No 32, 2016 | Restricted Materials Above Threshold |
| EU REACH Regulation (EC) No. 1907/2006 | Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: DEC 2010 (44) SVHC > Threshold: Not Yet Reviewed |
| Halogen Content | Not Low Halogen - contains Br or Cl > 900 ppm. |
| Solder Process Capability | Not applicable for solder process capability |

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

Compatible Parts





Customers Also Bought




















Documents

Product Drawings

FOSM LEAD LC/DPX ODVA - LC/DPX 20M

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2-2061348-0_E.2d_dxf.zip



English

Customer View Model

ENG_CVM_CVM_2-2061348-0_E.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2-2061348-0_E.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Application Specification

English