The StackiCap[™] range offers a significant reduction in 'PCB real estate' for an equivalent capacitance value when board space is at a premium.

Syfer's unique patent pending* construction and FlexiCap[™] termination material make the StackiCap[™] range suitable for applications including: power supplies, lighting, aerospace electronics and high voltage applications where a large amount of capacitance is required. Further developments are on-going, please contact the Sales Office for details of the full range. * Patent application No. 1210261-2 applies.



Maximum capacitance Up to 5.6μF Maximum voltage Up to 2kV

Comparison chart - StackiCap™ capacitors

Chip Size	Voltage	StackiCap™ range (nF)	Non- StackiCap™ range (nF)	Replaces Case Size
	200/250V	1000	680	2220
	500V	470	330	2220
1812	630V	330	180	2220
1012	1kV	180	100	2225 / 3640
	1.2kV	100	33	2225
	1.5kV	56	22	2225
	200/250V	2200	1000	3640
	500V	1000	560	3640
	630V	1000	330	5550
2220	1kV	470	120	8060
	1.2kV	220	82	5550
	1.5kV	150	47	5550
	2kV	100	27	8060
	200/250V	5600	3300	5550
	500V	2700	1000	8060
	630V	2200	680	8060
3640	1kV	1000	180	8060
	1.2kV	470	150	8060
	1.5kV	330	100	8060
	2kV	150	47	8060

Ordering information - StackiCap[™] capacitors

1812	Y	500	0474	J	X	т	WS2
Chip size	Termination	Voltage	Capacitance in picofarads (pF)	Capacitance tolerance	Dielectric	Packaging	Suffix code
1812 2220 3640	Y = FlexiCap [™] termination base with nickel barrier (100% matte tin plating). RoHS compliant. Lead free. H = FlexiCap [™] Termination base with nickel barrier (Tin/lead plating with minimum 10% lead). Not RoHS compliant.	200/250 = 200/250V 500 = 500V 630 = 630V 1K0 = 1kV 1K2 = 1.2kV 1K5 = 1.5kV 2K0 = 2kV	First digit is 0. Second and third digits are significant figures of capacitance code in picofarads (pF). Fourth digit is number of zeros eg. 0474 = 470nF Values are E12 series	J = ±5% K = ±10% M = ±20%	X = X7R	 T = 178mm (7") reel R = 330mm (13") reel B = Bulk pack tubs or trays 	WS2

Reeled quantities - StackiCap[™] capacitors

	1812	2220	3640
178mm (7") Reel	500/1,000	500/1,000	-
330mm (13") Reel	2,000/4,000	2,000/4,000	500

StackiCap

25