



- Ideal for securing, insulating, and routing cable and tubing.
- Cable and wire can be installed or removed for repair without removing clamp.
- Mounts with screws, mounting buttons or rivets.


Heyco® Nylon Wire Harness Clamps

MOUNTING HOLE DIAMETER		SCREW SIZE	PART DIMENSIONS						PART NO.	DESCRIPTION	STYLE	
			A		B		C					
			Bundle Dia.		Overall Length		Width		Natural			
in.	mm.		in.	mm.	in.	mm.	in.	mm.				
Snap Mouth *												
.157	4,0	#8	.50 .71	12,7 18,0	1.18 1.38	30,0 35,1	.39 .50	10,0 12,7	4127 4148	WHCX 500 WHCX 750	1	NEW!
Open Mouth												
.157	4,0	#8	.13	3,2	.77	19,5	.34	8,5	4149	WHC 125	2	NEW!
			.25	6,4	.83	21,0	.39	10,0	4126	WHCX 250	3†	
.205	5,2	#10	.25	6,4	.86	21,8	.41	10,4	4150	WHC 250	3	
			.38	9,0	.83	21,0	.40	10,2	4151	WHC 375		
			.50	12,5	1.16	29,4	.40	10,2	4152	WHC 500		
			.63	15,9	1.13	28,6	.50	12,7	4153	WHC 625		
			.75	19,1	1.28	32,5	.50	12,7	4154	WHC 750		
			1.00	25,4	1.53	38,9	.50	12,7	4210	WHC 1000		
			1.50	38,1	2.12	53,9	.50	12,7	4211	WHC 1500		


Standard color natural.

*Bundle Diameter in closed position.


†No reinforcing ribs on Part No. 4126.



Style 1



Style 2



Style 3





- Retainer clip allows clamp to be **pre-positioned** on hose before final installation.
- Double row of teeth for more secure grip.
- Quick and easy installation. Tighten instantly with hand pliers or Air Tool (on page 7-37).
- Reusable. Can be removed without cutting.
- Supertough nylon clamps offer additional clamping strength.
- Outlast tubing under pressure.
- Non-conductive and non-magnetic.
- No moving pieces to seize or vibrate loose.
- Maximum Pressure Rating: 200 PSI.

Heyco® Nylon Locket™ Hose Clamps

EFFECTIVE CLAMP RANGE				PART NO.	DESCRIPTION	PART DIMENSIONS			
Minimum Diameter		Maximum Diameter				A Clamp Thickness		B Strap Thickness	
in.	mm.	in.	mm.			in.	mm.	in.	mm.
						Black			
LHC Series									
.34	8,7	.41	10,3	2388	LHC 344	.25	6,4	.08	2,0
.53	13,5	.59	15,1	2391	LHC 531				
.67	17,0	.81	20,6	2393	LHC 672				

Standard color black.



Quick Specs

	WHCX & WHC	LHC
Material	Nylon 6/6	Nylon 6/6 Supertough
Flammability Rating	94V-2	94HB
Temperature Range	32°F (0°C) to 185°F (85°C)	32°F (0°C) to 185°F (85°C)