

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [0502128000](#)
Status: **Active**
Overview: [Micro-Latch Wire-to-Board Connector System](#)
Description: 2.00mm Pitch, Micro-Latch Female Crimp Terminal, Tin (Sn) Plating, 24-30 AWG, Reel

Documents:

3D Model (PDF)	Product Specification PS-51090-018-001 (PDF)
3D Model	Product Specification PS-51160-001 (PDF)
Drawing (PDF)	Product Specification PS-51160-006-001 (PDF)
Product Specification PS-35507-002-001 (PDF)	Product Specification PS-51225-003-001 (PDF)
Product Specification PS-51065-005 (PDF)	Product Specification PS-52968-006-001 (PDF)
Product Specification PS-51065-016-001 (PDF)	Product Specification PS-52968-007-001 (PDF)
Product Specification PS-51065-017-001 (PDF)	Product Specification PS-53358-001-001 (PDF)
Product Specification PS-51065-018-001 (PDF)	Product Specification PS-53717-002-001 (PDF)
Product Specification PS-51089-001 (PDF)	Product Specification PS-54111-001 (PDF)
Product Specification PS-51089-005-001 (PDF)	Product Specification PS-54111-002-001 (PDF)
Product Specification PS-51090-003 (PDF)	Product Specification PS-54452-006-001 (PDF)
Product Specification PS-51090-004-001 (PDF)	Product Specification PS-55533-004-001 (PDF)
Product Specification PS-51090-005-001 (PDF)	Application Specification 510900001-000 (PDF)
Product Specification PS-51090-009 (PDF)	Packaging Specification SPK-50212-001-001 (PDF)
Product Specification PS-51090-016-001 (PDF)	RoHS Certificate of Compliance (PDF)
Product Specification PS-51090-017-001 (PDF)	Product Literature (PDF)

General

Product Family	Crimp Terminals
Series	50212
Application	Automotive, Signal, Wire-to-Board
Crimp Quality Equipment	Yes
Overview	Micro-Latch Wire-to-Board Connector System
Packaging Alternative	502128100 (Loose)
Product Name	DuraClik, Mi II, Micro-Latch, Sherlock
UPC	800753644625

Physical

Gender	Female
Material - Metal	Phosphor Bronze
Material - Plating Mating	Tin
Material - Plating Termination	Tin
Net Weight	20.400/mg
Packaging Type	Reel
Termination Interface: Style	Crimp or Compression
Wire Insulation Diameter	1.40mm max.
Wire Size AWG	24, 26, 28, 30
Wire Size mm ²	N/A

Electrical

Current - Maximum per Contact	2.0A
Voltage - Maximum	125V

Material Info

Reference - Drawing Numbers

Application Specification	510900001-000
Crimp Specification	CS-50212
Packaging Specification	SPK-50212-001-001
Product Specification	PS-35507-002-001, PS-51065-005, PS-51065-016-001, PS-51065-017-001, PS-51065-018-001, PS-51089-001, PS-51089-005-001, PS-51090-003, PS-51090-004-001,



Series image - Reference only

EU ELV

Compliant

EU RoHS

Compliant

REACH SVHC

Not Contained Per -
ECHA_01_2020 (16
January 2020

Halogen-Free

Status

Low-Halogen

For more information, please visit [Contact US](#)

China ROHS

ELV

RoHS Phthalates

China RoHS

Green Image

Compliant

Not Contained

Search Parts in this Series

[50212](#) Series

Use With

DuraClik Receptacle Housing [502351](#)

Micro-Latch Receptacle Housing [51065](#)

Mi II Receptacle Housings [51089](#) ,
[51090](#)

Application Tooling | FAQ

Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.

Global

Description	Product #
Extraction Tool	11030043
Hand Crimp Tool for 2.00mm Pitch Terminal, 24-30 AWG	638190500
FineAdjust Applicator for 2.00mm Pitch Wire-to-Board	639005200

Sales Drawing

PS-51090-005-001, PS-51090-009, PS-51090-016-001,
PS-51090-017-001, PS-51090-018-001, PS-51160-001,
PS-51160-006-001, PS-51225-003-001,
PS-52968-006-001, PS-52968-007-001,
PS-53358-001-001, PS-53717-002-001,
PS-54111-001, PS-54111-002-001, PS-54452-006-001,
PS-55533-004-001
SD-50212-001

Crimp Terminals,
24-30 AWG Wire,
Insulation OD
1.10-1.30mm
FineAdjust Applicator 639046800
for 2.00mm Pitch
Wire-to-Board Crimp
Terminal, 24-30
AWG, Insulation OD
0.90-1.10mm
T2 Terminator Die 639105200

Japan
Description **Product #**

Extraction Tool 571056000
Applicator for M211A 571753000
Bench Press, 22-30
AWG Wire
S-1 Applicator 571753720
for Wire-to-Board
Receptacle Terminal,
for 24-30 AWG
Twisted Wire

This document was generated on 04/08/2020
PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION