


Customers:		Edition: A	Revision: 0
Customer Part No.:		BCc Part No.: D391K20Y5PH63L2R	
Rated Voltage: 100 VDC	Test Voltage: 250 VDC	12NC:	Qualification: IEC
Capacitance: 390.00pF	Tolerance: ± 10%	Cap.Range: 351.00pF To 429.00pF	
DF/Q: 2.5% MAX	At 1KHZ/1.0VRMS	Temp.chart./coefficient: Y5P	Operating Temp.: -30°C to 125°C
Coating: Phenolic	SPQ: 1000PCS	Insulation Resistance: 10G Ω MIN AT 100 VDC	
Marking: <u>391</u>		Dimensions(mm)	
		D-Body Diameter: 5.00 MAX	
		T-Body Thickness: 3.50 MAX	
		F-Lead Spacing: 2.50±0.80	
		V-S Spacing: NA	
		L-Lead Length: 30.00±5.00	
		SH-Seat Height: NA	
		DR-Run Down: 1.50 MAX	
		ED-Disc Exposure: NA	
		K-Kink Off: NA	
Resistance to Soldering Heat: 260±5°C, 10±1s		θ-Kink Angle: NA	
Packing: BULK		Lead Style: L	
Taping Specifications(mm)			
Pitch between Components	P		
Feed-hole Pitch	P0		
Feed-hole Diameter	D0		
Height to Seating Plane	H0		
Top of Component Height	H1		
Carrier Tape Width	W		
Remarks/Customers specific requirements:			