

Note: This datasheet may be out of date.

Please :lownload the latest datasheet of GCG1555G1H4R5BA01# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-US/products/productdetail?partno=GCG1555G1H4R5BA01%23

GCG1555G1H4R5BA01#

"#" indicates a package specification code.
















Limited to conductive give mounting

< List of part numbers with package codes > GCG1555G1H4R5BA01J GCG1555G1H4R5BA01W GCG1555G1H4R5BA01D



Appearance & Shape







Packaging	Specifications	Minimum Order Quantity
J	330mm Paper Tape	50000
W	180mm Paper Tape (W8P1)	20000
D	180mm Paper Tape	10000

Mass (typ.)		
1 piece	1.6mg	
φ180mm Reel	118g	



Limited to Conductive Glue Mounting

1 of 2

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





Note: This datasheet may be out of date. Please download the latest datasheet of GCG1555G1H4R5BA01# from the official website of Murata Manufacturing Co., Ltd.

"#" indicates a package specification code.

GCG1555G1H4R5BA01#

Specifications

Length	1.0±0.1mm
Width	0.5±0.05mm
Thickness	0.5±0.05mm
Capacitance	4.5pF ±0.1pF
Distance between external terminals g	0.3mm min.
External terminal size e	0.15 to 0.35mm
Operating Temperature Range	-55°C to 150°C
Rated Voltage	50Vdc
Size code in inch(mm)	0402 (1005M)
TC	0±30ppm/°C
Temperature characteristics (complied standard)	X8G(Murata)
Temperature range of temperature characteristics	25°C to 150°C

2 of 2

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

