

GMA05XR72A221MA01#

“#” indicates a package specification code.

In Production

General

RoHS


REACH

125 °C max.

Bonding

< List of part numbers with package codes >
GMA05XR72A221MA01T

Appearance & Shape



References

Packaging	Specifications	Minimum Order Quantity
T	Bulk(Bag)	400

Mass (typ.)	
1 piece	0.5mg

Attention
1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
2.This datasheet has only typical specifications because there is no space for detailed specifications.
Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

GMA05XR72A221MA01#

“#” indicates a package specification code.

Specifications

Length	0.5±0.05mm
Width	0.5±0.05mm
Thickness	0.35±0.05mm
Capacitance	220pF ±20%
Operating Temperature Range	-55°C to 125°C
Rated Voltage	100Vdc
Size code in inch(mm)	0202 (0505M)
Capacitance change rate	±15.0%
Temperature characteristics (complied standard)	X7R(EIA)
Temperature range of temperature characteristics	-55°C to 125°C

Attention
1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
2.This datasheet has only typical specifications because there is no space for detailed specifications.
Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.