

GRM0335C1H220GA01#

Reflow OF Ultra-compact © Complies with RoHS Recommended

< List of part numbers with package codes >

GRM0335C1H220GA01D , GRM0335C1H220GA01J , GRM0335C1H220GA01C , GRM0335C1H220GA01B

Shape





"#" indicates a package specification code.

References

_		
Packaging	Specifications	Minimum quantity
D	Paper tape (180mm)	15000
J	Paper tape (330mm)	50000
С	Bulk case	50000
В	Packing in bulk	1000

L size	0.6 ± 0.03mm
W size	0.3 ± 0.03mm
T size	0.3 ± 0.03mm
External terminal width e	0.1 to 0.2mm
Distance between external terminals g (Min.)	0.2mm
Size code in mm(inch)	0603 (0201)

Mass (typ.) 0.33mg 1 piece Reel (180mm) 118g

Specifications

Capacitance	22pF ±2%
Rated voltage	50Vdc
Temperature characteristics (complied standard)	COG(EIA)
Temperature coefficient	0 ± 30ppm/
Temperature range of temperature characteristics	25 to 125
Operating temperature range	-55 to 125

🔔 Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it 's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



URL : http://www.murata.co.jp/

Last updated: 2013/03/08

Chart of characteristic data (The charts below may show another part number which shares its characteristics.)





DC bias characteristics



Capacitance - temperature characteristics







AC voltage characteristics



2 of 2

This PDF data has only typical specifications because there is no space for detailed specifications.

Therefore, please reviewour product specifications or consult the approval sheet for product specifications before ordering.

