Note: This datasheet may be out of date.

Please download the latest datasheet of GRM31C7U2J392JW32# from the official website of Murata Manufacturing Co., Ltd.

anulaciumi Go., Liu.

http://www.murata.com/en-US/products/productdetail?partno=GRM31C7U2J392JW32%23

GRM31C7U2J392JW32#

"#" indicates a package specification code.














< List of part numbers with package codes > GRM31C7U2J392JW32K GRM31C7U2J392JW32L



Appearance & Shape







Packaging	Specifications	Minimum Order Quantity
K	330Embossed Tape	8000
L	180Embossed Tape	2000

Mass (typ.)	
1 piece	38mg
φ180mm Reel	116g

1 of 4

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





Note: This datasheet may be out of date. ${\it Please \ download \ the \ latest \ data sheet \ of \ GRM31C7U2J392JW32\# from \ the \ official \ website \ of \ Murata}$ Manufacturing Co., Ltd.

GRM31C7U2J392JW32#

"#" indicates a package specification code.



Length	3.2±0.2mm
Width	1.6±0.2mm
Thickness	1.6±0.2mm
Capacitance	3900pF ±5%
Distance between external terminals g	1.5mm min.
External terminal size e	0.3mm min.
Operating Temperature Range	-55°C to 125°C
Rated Voltage	630Vdc
Size code in inch(mm)	1206 (3216M)
TC	-750±120ppm/°C
Temperature characteristics (complied standard)	U2J(EIA)
Temperature range of temperature characteristics	25°C to 125°C

2 of 4

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.






Note: This datasheet may be out of date Please download the latest datasheet of GRM31C7U2J392JW32# from the official website of Murata Manufacturing Co., Ltd.


GRM31C7U2J392JW32#

"#" indicates a package specification code.





The charts below may show another part number which shares its characteristics.





GRM31C7U2J392JW32 R DCOV, 25degC





3 of 4

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





Note: This datasheet may be out of date Please download the latest datasheet of GRM31C7U2J392JW32# from the official website of Murata Manufacturing Co., Ltd.

oductdetail?partno=GRM31C7U2J392JW32%23

GRM31C7U2J392JW32#

"#" indicates a package specification code.





4 of 4

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

