Note: This datasheet may be out of date. Please download the latest datasheet of GRT31CR61E335KE01# from the official website of Murata Manufacturing Co., Ltd.

GRT31CR61E335KE01#

"#" indicates a package specification code.


















< List of part numbers with package codes > GRT31CR61E335KE01L GRT31CR61E335KE01K



Appearance & Shape







References

Packaging	Specifications	Minimum Order Quantity
L	180Embossed Tape	2000
К	330Embossed Tape	6000

Mass (typ.)	
1 piece	52mg
φ180mm Reel	144g



Derating1

1 of 4

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





GRT31CR61E335KE01#

Note: This datasheet may be out of date. Please download the latest datasheet of GRT31CR61E335KE01# from the official website of Murata Manufacturing Co., Ltd.

"#" indicates a package specification code.



Length	3.2±0.2mm
Width	1.6±0.2mm
Thickness	1.6±0.2mm
Capacitance	3.3µF ±10%
Distance between external terminals g	1.5mm min.
External terminal size e	0.3 to 0.8mm
Operating Temperature Range	-55°C to 85°C
Rated Voltage	25Vdc
Size code in inch(mm)	1206 (3216M)
Capacitance change rate	±15.0%
Temperature characteristics (complied standard)	X5R(EIA)
Temperature range of temperature characteristics	-55°C to 85°C

2 of 4

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





GRT31CR61E335KE01#


"#" indicates a package specification code.




The charts below may show another part number which shares its characteristics.









GRT31CR61E335KE01 C-DC bias capchange, 25.0degC, AC1.

AC Voltage[Vrms] GRT31CR61E335KE01 C-AC Voltage capchange, DCOV, 25.0d

3 of 4

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





Note: This datasheet may be out of date. Please download the latest datasheet of GRT31CR61E335KE01# from the official website of Murata Manufacturing Co., Ltd.

oductdetail?partno=GRT31CR61E335KE01%23

GRT31CR61E335KE01#

"#" indicates a package specification code.





4 of 4

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

