LE910Cx Linux

LTE Cat.4 150/50 - Cat.1 10/5



Product Description

The LE910Cx series of 4G LTE modules are compliant with the 3GPP Release 10 and are available with optional quad-constellation GNSS capability. This compact LGA form factor family is available in a variety of configurations, supporting both single-mode and fallback as needed for specific regions, carriers, and use cases.

Key Benefits

- Best-in class 3GPP rel10 platform
- MTC features ready according to 3GPP Rel.12
- Easy to integrate with peripherals and actuators using USB 2.0 HS, UART and user definable GPIOs
- Internet friendly with integrated TCP/IP and UDP/IP stacks
- Simple drop-in migration and technology design reusepath to 2G and 3G with any xE910 module
- Over-the-Air firmware update
- Embedded GNSS solution

Family Concept

The LE910Cx is a member of Telit's flagship xE910 module family delivering 4G radio access technology in the 28.2 x 28.2 x 2.2 mm family form factor. The Telit Cinterion xE910 Unified Form Factor Family is comprised of 2G, 3G, and 4G, 3GPP and 3GPP2 products sharing a common form factor as well as electrical and programing interfaces which allows developers to implement a "design once, use anywhere" strategy.

Variants

- Cat.4 and Cat.1 4G North American market - AT&T, Verizon and T-Mobile

- Cat.1 4G North American market for Sprint (LTE single-mode) and AT&T (with the addition of global roaming capabilities due to 3G/2G fallback).

- Cat.1 4G with 3G fallback for APAC optimized for the ANZ region and Japan.

- Cat.4 and Cat.1 4G with 3G/2G fallback for Europe with full coverage for EU market

- Cat.4 and Cat.1 4G with 2G fallback for India market

IoT Connectivity and Portal Ready

This product is capable of supporting the extensive suite of Value Added Services from IoT Connectivity including Module Management and others which make the management of IoT deployments under mobile networks effective, enhancing profitability and reliability. It is also Portal-ready which means that the AT command library in this module includes a set of high-level commands designed exclusively for quick and hassle-free on-boarding of the device to the portal and to back-end systems and servers.

AVAILABLE FOR

- North America
- Australia
- Europe
- Japan
- India

LE910Cx Linux

Variants

	LE910C1/C4-EU	LE910C1/C4-NF/-NFD	LE910C1/C4-IN
Market	EMEA	North America (Public safety, AT&T, FirstNet, T-Mobile, Verizon + Canada)	India
Frequencies			
4G bands (MHz)	B1, B3, B7, B8, B20, B28A	B2, B4, B5, B12 B13, B14, B66, B71	B1, B3,B5, B8, B40,B41
3G bands (MHz)	B1, B3, B8	B2, B4, B5	-
2G bands (MHz)	B3,B8		B3,B8
Voice	VoLTE/3G/2G	VoLTE/3G (only -NF version)	-

Product Features

- Band 14 support
- LTE FDD Cat.4, 3GPP release 10 compliant
- LTE FDD Cat.1. 3GPP release 9 compliant
- Rx Diversity and MIMO DL 2x2
- Single Rx option
- VoLTE support
- SMS over IMS
- Built in UDP/TCP/FTP/SMTP stack
- IPv4/IPv6 stack
- Control via AT commands according to 3GPP
- TS 27.005, 27.007 and Telit Cinterion Custom AT commands
- SIM application Tool Kit
- OMA-DM Telit Cinterion Software Management
- Simultaneous support of GPS, Glonass, Beidou, Galileo, QZSS

Hardware and Electrical Specifications

- Dimensions 28.2 x 28.2 x 2.2mm
- 181-pin LGA interface
- 10 I/O ports (@1.8V) including multifunctional I/Os
- USB 2.0 HS / HSIC
- UART
- SPI
- PCM
- I2C
- 1.8 V / 3V SIM interface
- RF pad, RX Div. & MIMO pad
- Temperature Range Industrial:
  -40°C to +85°C
- REACH and RoHS compliant
- Output power
  - Class 3 (0.2 W, 23 dBm) @ LTE
- Supply voltage range:
  - Nominal: 3.8 VDC
  - Range: 3.4 - 4.2 VDC

Data

LTE Cat. 4

- Uplink up to 50 Mbps
- Downlink up to 150 Mbps

DC-HSPA+ 42 Mbps

LTE Cat. 1

- Uplink up to 5 Mbps
- Downlink up to 10 Mbps

Approvals

- FCC/ISED, PTCRB, MNOs (North America)
- RCM (Australia)
- RED/GCF (Europe)
- RL/JTBL (Japan)
- Enacom, Anatel, CRC, MTC (Latin America)
- CCC/SRRC (China)

QUESTIONS? VISIT WWW.TELIT.COM/CONTACT-US

Like Us on Facebook | Follow Us on LinkedIn | Follow Us on X | Subscribe to Our Channel

[11.2026]

Telit Cinterion reserves all rights to this document and the information contained herein. Products, names, logos and designs described herein may in whole or in part be subject to intellectual property rights. The information contained herein is provided "as is." No warranty of any kind, either express or implied, is made in relation to the accuracy, reliability, fitness for a particular purpose or content of this document. This document may be revised by Telit Cinterion at any time. For most recent documents, please visit www.telit.com.

Copyright © 2026, Telit Cinterion