

# LLL185R60J225ME14#

“#” indicates a package specification code.

In Production

General

RoHS

REACH


85 °C max.

Low ESL

Reflow OK

< List of part numbers with package codes >  
LLL185R60J225ME14L LLL185R60J225ME14K

## Appearance & Shape



## References

Packaging	Specifications	Minimum Order Quantity
L	180Embossed Tape	4000
K	330Embossed Tape	10000

Mass (typ.)	
1 piece	3.9mg
φ180mm Reel	100g

**Attention**  
1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.  
2.This datasheet has only typical specifications because there is no space for detailed specifications.  
Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

# LLL185R60J225ME14#

“#” indicates a package specification code.

## Specifications

Length	0.8±0.1mm
Width	1.6±0.1mm
Thickness	0.5+0.05/-0.1mm
Capacitance	2.2μF ±20%
Distance between external terminals g	0.1mm min.
External terminal size e	0.25±0.15mm
Operating Temperature Range	-55°C to 85°C
Rated Voltage	6.3Vdc
Size code in inch(mm)	0306 (0816M)
Capacitance change rate	±15.0%
Temperature characteristics (complied standard)	X5R(EIA)
Temperature range of temperature characteristics	-55°C to 85°C

### Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.