MPT35C330RF ACTIVE

CGS | CGS MPT

TE Internal #: 6-2176430-2


Power Resistor, Thick Film, TO220, 35 W, 330 Ω , 1 %, ± 50 ppm/°C, Radial-Leaded, Copper Termination, 10.16 x 15 x 4.6 mm, Tube, 2

Termination, CGS MPT

View on TE.com >



Passive Components > Resistors > Through-Hole Resistors



Resistor Type: Power Resistor
Element Type: Thick Film

Package Size Code: TO220

Power Rating: 35 W

Resistance Class: Up to $1k\Omega$

Features

Product Type Features

Troduct Type readures	
Resistor Type	Power Resistor
Element Type	Thick Film
Package Size Code	TO220
Configuration Features	
Number of Resistors	1
Electrical Characteristics	
Operating Voltage	350 V
Power Rating	35 W
Resistance Class	Up to $1k\Omega$
Resistance Value	330 Ω
Passive Component Tolerance	1 %
Body Features	

Radial-Leaded

Lead Type



Termination Features

Termination Area Base Material	Copper
Number of Terminations	2
Dimensions	
Passive Component Dimensions	10.16 x 15 x 4.6 mm
Usage Conditions	
Temperature Coefficient	±50 ppm/°C
Packaging Features	
Packaging Method	Tube

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) SVHC > Threshold: Pb (92.5% in Component Part) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach




Compatible Parts






Also in the Series | CGS MPT




Customers Also Bought











Documents

Product Drawings
MPT35 330R 1%

English

CAD Files

Power Resistor, Thick Film, TO220, 35 W, 330 Ω , 1 %, ± 50 ppm/°C, Radial-Leaded, Copper Termination, 10.16 x 15 x 4.6 mm, Tube, 2 Termination, CGS MPT



3D PDF

3D

Customer View Model

ENG_CVM_CVM_6-2176430-2_BA.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_6-2176430-2_BA.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_6-2176430-2_BA.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions**of use

Datasheets & Catalog Pages

MPT-0518

English