

VI/VJ



End Stackable  
02 2 contacts  
03 3 contacts  
.. ...  
24 24 contacts  
(pitch 5.0&5.08)  
16 16 contacts  
(pitch 7.5&7.62)  
12 12 contacts  
(pitch 10.0&10.16)  
08 8 contacts  
(pitch 15.0&15.24)

0 5.0/.197"  
1 10.0/.394"  
2 5.08/.20"  
3 10.16/.40"  
4 7.5/.295"  
5 15.0/.591"  
6 7.62/.30"  
(only VJ)  
7 15.24/.60"  
(only VJ)

0 "+/-" Combination type  
W/Brass Machined Clamp  
1 "- " Slotted screw  
W/Brass Machined Clamp

0 Black  
5 Green  
(RAL 6018/T)  
6 Blue  
8 Grey  
(RAL 7035/D)  
C Green  
(RAL 6018/U)

0 90D wire inlet(Vertical)  
1 180D wire inlet(with cover)  
(Horizontal)  
2 180D wire inlet(without cover)  
(Horizontal)  
3 90D wire inlet(Vertical)-  
Solid block  
4 180D wire inlet(with cover)  
(Horizontal)-Solid block  
5 180D wire inlet(without cover)  
(Horizontal)-Solid block

0000 Standard  
(Steel screw plating Cr<sup>III</sup>)  
Any special item by  
customer request,  
please contact sales  
department.

G ROHS compliant  
(lead<4%)  
In copper alloy  
  
H ROHS compliant  
(lead<1000ppm)  
In copper alloy